Sharp Signage Display

Sharp MultiSync® M752 LCD 75" Message Large Format Display

The versatile solution for professional display applications, the Sharp MultiSync® M2 Series (32" up to 98") is purpose-built for demanding signage and meeting room environments.

- Seamless meeting workflows – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups. As the established standard for modern collaboration spaces, USB-C supports frictionless BYOD experiences.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Enhanced imaging precision – when brand consistency and corporate identity are important, Sharp's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Broad AV compatibility – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration and future-proof scalability.

Specifications

Panel Data

Panel Response Time (ms)	8

Display Module Data

Panel Technology	IPS with Direct LED backlights
Native Resolution (Pixels)	3840 x 2160
Aspect Ratio	16:9
Brightness (cd/m²)	550
Contrast Ratio	8000:1
Viewing Angle (°)	178
Colour Depth [bn]	1073 (10bit)
Response Time (typ.) [ms]	8

Resolution

Supported Resolution	1024 x 768 , 1920 x 1200, 1400 x 1050, 1366 x 768, 720 x 480, 720 x 400, 720 x 576, 1360 x 768, 3840 x 2160, 4096 x 2160, 1680 x 1050, 1280 x 720, 800 x 600, 640 x 480, 1920 x 1080, 1600 x 1200, 1280 x 1024, 1440 x 900, 1280 x 800

Accessories

Accessories	Remote Control , Eco Sensor, Feet, Wall mount, USB-C cable, Trolley, Speaker
Shipping Content	Power Cable, Remote Control, HDMI Cable, 2 x AAA batteries, Setup Manual, Display

Weights and Measures

Shipping Carton Dimensions (Width) mm	1830
Shipping Carton Dimensions (Height) mm	1070
Shipping Carton Dimensions (Depth) mm	225
Shipping Weight (Kg)	51

Connectivity

Digital	DisplayPort, DisplayPort out, HDMI, USB Type C
Output Control	LAN 100Mbit

Ergonomics

Landscape Dimensions (Width) [mm]	1683
Landscape Dimensions (Height) [mm]	961
Landscape Dimensions (Depth) [mm]	83

Synchronisation Rate

Horizontal Frequency [kHz]	15 - 135
Vertical Frequency [Hz]	23 - 76

Environmental Conditions

Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80

Projectors

Weight (g)	38

Power Supply and Operating Environment

Operating Voltage (ACV)	100-240
Frequency (Hz)	50-60
Via AC Adapter	True
Operating Voltage (DCV)	100-240
Operating Temperature (°C)	0 - 40
Storage Temperature (°C)	-20 - 60
Storage Humidity Min [%]	10
Storage Humidity Max [%]	80
Power Saving Mode (W)	< 2 (Networked Standby)

Additional Features

Colour Versions	Black Back Cabinet
Safety and Ergonomics	EMC Class B, UKCA, RoHS, UL/C-UL or CSA, FCC Class B, CE, EnergyStar 8.0, REACH
Warranty	optional 4th to 5th year warranty extension, Additional services available, 3 years warranty incl. backlight

Installation

Portrait Installation	True
Landscape Installation	True
Mounting (VESA mm)	600 x 400 (FDMI)
Mounting (Number of Points/Pitch)	4
Mounting Screw Specification (Size/Max Length)	M8
Face up	True

Key Specifications

Special Characteristics	CEC Support, DICOM Simulation, Clone Settings, HDMI ARC, Scheduler
24/7 Operation Certified	True
Built in Speakers (W)	10 + 10

Display

Screen Size (inch)	75
Screen Size (cm)	190
Colour Gamuts	72% NTSC

Mechanical

Bezel Width (Left/Right) [mm]	14
Bezel Width (Upper) [mm]	14
Bezel Width (Lower) [mm]	15

Green Features

Energy Efficiency	LED backlight technology, Energy efficiency class: G
Ecological Standards	Energy Star 8.0

Electrical

Power Consumption on Mode [W]	140 (shipping)
Power Supply	100-240 V

Touch Interface Specification

Haze Level [%]	Pro 25

Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logotypes are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync® M752 LCD 75" Message Large Format Display, 14/7/2026