

Sharp signage kijelző

Sharp MultiSync P656



Purpose-designed for control rooms, passenger information, and prestige retail or corporate signage, the P6 Series delivers uncompromising performance, day after day.

- Enhanced imaging precision – NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment.
- Security assured – 802.2x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- Mission-critical performance – the P6 series is engineered to deliver lasting clarity and durability in challenging environments without the need for bulky housings.
- Trusted integration – full compatibility with major AV ecosystems, including Crestron XiO Cloud and NVX, Q-Sys, Cisco Webex, Matrox IPMX, and CMS solutions, ensures seamless setup and scalability.

Műszaki jellemzők

Panel Technológia	IPS with Direct LED backlights
Képarány	16:9
Fényerő (cd/m2)	700
Kontrasztarány	8000:1
Képpont távolság (mm H/V)	0,372
Viewing Angle [°]	178
Colour Depth [bn]	1073 (10bit)
Aktív képernyő felület (H/V) mm	1428.48 x 803.52
Üzemi feszültség (ACV) / Frekvencia (Hz)	100-240
Üzemi feszültség (ACV) / Frekvencia (Hz)	50-60
Energiafogyasztás (W) (Használat közben MAX)	160
Üzemi hőmérséklet (oC)	0 - 40
Storage Temperature [°C]	-20 - 60
Storage Humidity [%]	10
Storage Humidity [%]	80
Keret mérete (B/J) mm	11
Keret mérete (U) mm	11
Keret mérete (L) mm	14
DisplayPort	1
HDMI	2
Operating Humidity (min) [%]	20
Operating Humidity (max) [%]	80
Haze Level [%]	Pro 25

Special Characteristics	DICOM szimuláció, CEC Support, HDMI ARC, Scheduler
24/7 működés	True
Local Dimming	True
Energiaigazdálkodás	True
Eszköz tér (Felszereléshez)	True
Hőmérséklet érzékelő	True
Fényerő érzékelő	True
Szellemkép csökkentés funkció	True
Időzítő	True
Távoli kezelés	True
Erősítés szabályozás	True
SNMP	True
Fekvő elrendezés	True
Álló elrendezés	True
Vízszintes	True
Felszerelés (VESA/pontok száma/pitch mm)	400 x 400 (FDMI)
Felszerelő csavarok tulajdonságai (Méret/Max. hosszúság)	M6
Termék súlya állvány nélkül (Kg)	26
Szállítási súly (Kg)	35
Képátló (hüvelyk / cm)	64
Képátló (hüvelyk / cm)	163
Gyártói jótállás (év)	3 év garancia a háttérvilágításra is kiterjedően



Design and specifications are subject to change without prior notice. All information was correct at time of print. Microsoft, Excel, PowerPoint, OneDrive, SharePoint, Active Directory, Windows Server, and Windows are either registered trademarks or trademarks of Microsoft Corporation in the US and/or other countries. Adobe and PostScript 3 are either registered trademarks or trademarks of Adobe Systems Incorporated in the US and/or other countries. Google Drive, Gmail, Android, and Google Cloud Print are trademarks of Google LLC. The Google Drive trademark is used with permission from Google LLC. Box is a trademark, service mark, or registered trademark of Box, Inc. QR Code is a registered trademark of DENSO WAVE INCORPORATED in Japan and other countries. AirPrint and Mac are trademarks of Apple Inc., registered in the US and other countries. PCL is a registered trademark of Hewlett_x0002_Packard Company. Qualcomm DirectOffice is a product of Qualcomm Technologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of Qualcomm Incorporated, registered in the US and other countries. DirectOffice is a trademark of CSR Imaging US, LP, registered in the US and other countries. All other company names, product names and logos are trademarks or registered trademarks of their respective owners. ©Sharp Corporation All trademarks acknowledged. E&O. Ref: Sharp MultiSync P656, 14/7/2026